

400nm~410nm 40mW PM Fiber Coupled Diode Laser With TEC Cooler | Violet Laser Diode Module
405nm 40mW Pigtailed Laser Module with Polarization Maintaining Fiber |HHL Package with PD| High Stability
WSLX-405-040m-PM-H8-T-PD **Wavespectrum Laser Group** **en.wavespectrum-laser.com.cn**

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	+10 ~ +30	°C
Storage Temperature	T_{stg}	-20 ~ +80	°C
Lead soldering temperature (10 sec.)	T_{is}	260	°C

Features:

- 405nm
- 3um UV PM Fiber
- Built-in TEC Cooling
- 8-Pin Package

Applications:

- Medical Laser Treatment
- Biotechnology
- Others



Specifications


WSLX-405-040m-PM-H8-T-PD

	Min.	Type	Max.
Center Wavelength@25°C	405nm±10nm		
Spectral Width (FWHM)	----	2nm	----
Output Power	----	40mW	----
Recommend Operating Temperature	25 °C		
Threshold Current (Typ.)	----	45mA	80mA
Operating Current (Typ.)	----	125mA	140mA
Operating Voltage		5.0V	6.0V
Polarization Extinction Ratio	13dB	15dB	
TEC Max Current	1.3A		
TEC Max Voltage	4.0V		
Thermistor	10K		
Fiber Type	Polarization Maintaining Fiber		
Fiber Core	3um		
Fiber Length	>80cm		
Connector Type	FC/APC		


High Polarization Extinction Ratio (PER) Version Laser Module is also available, please contact us.



8-Pin Package View:



Pin Out:



PIN	FUNCTION	PIN	FUNCTION
1	RT	5	PD(+)
2	LD(-)	6	NC
3	LD(+)&PD(-)	7	TEC(-)
4	RT	8	TEC(+)

Wavespectrum offer Customized 405nm Fiber Coupled LD.

- Customized Output Power
- Customized Fiber Core
- Dual-Wavelength or Tri-Wavelength Module Optional
(such as 2W@405nm+ 10W@980nm)

Contact us with info@wavespectrum-laser.com

Electrically shorten LD module and store in non-extreme conditions.

Suggest using the constant current power supply.



Wavespectrum Laser Group
www.wavespectrum-laser.com
sales@wavespectrum-laser.com

